



CO-CONSTRUCT

Services Integration with Concrete Buildings



Guidance for a defect-free interface

By Roderic Bunn, Deryk Simpson and Stephen White

Interface
Engineering
Publications is a
Co-Construct
initiative
supported by

dti

BSRIA
MAX FORDHAM





CO-CONSTRUCT



What is Co-Construct?

Co-Construct is a network of five leading construction research and information organisations – Concrete Society, BSRIA, CIRIA, TRADA and SCI – who are working together to produce a single point of communication for construction professionals.

BSRIA covers all aspects of mechanical and electrical services in buildings, including heating, air conditioning, and ventilation. Its services to industry include information, collaborative research, consultancy, testing and certification. It also has a worldwide market research and intelligence group, and offers hire calibration and sale of instruments to the industry.

The Construction Industry Research and Information Association (CIRIA) works with the construction industry to develop and implement best practice, leading to better performance. CIRIA's independence and wide membership base makes it uniquely placed to bring together all parties with an interest in improving performance.

The Concrete Society is renowned for providing impartial information and technical reports on concrete specification and best practice. The Society operates an independent advisory service and offers networking through its regions and clubs.

The Steel Construction Institute (SCI) is an independent, international, member-based organisation with a mission to develop and promote the effective use of steel in construction. SCI promotes best practice through a wide range of training courses, publications, and a members advisory service. It also provides internet-based information resources.

TRADA provides timber information, research and consultancy for the construction industry. The fully confidential range of expert services extends from strategic planning and market analysis through to product development, technical advice, training and publications.

For more information on Co-Construct visit www.construction.co.uk.

Services Integration with Concrete Buildings

Copyright of all material in this publication rests with The Concrete Society and BSRIA. Guidance appearing in the green text boxes is copyright The Concrete Society Ltd, while all guidance in blue text boxes is copyright BSRIA. Case study material was kindly supplied by Max Fordham LLP. Additional input was provided by John Clarke and Richard Day and Neil Crook from The Concrete Society, Ian Haining from Costain and John Payne from Edmund Nuttal.

Photographs and illustrations in this publication were provided by BSRIA and The Concrete Society unless otherwise credited.

Cover Illustration: The concrete barrel-vault moulding process for the SAS Building, showing chilled water pipework fitted to steel re-enforcement prior to the concrete pour. Copyright Max Fordham LLP.



This publication was part-funded by the Department of Trade and Industry under the Partners In Innovation (PII) collaborative research programme. The views expressed in this publication are not necessarily those of the DTI. Final editorial control and publishing responsibility of this publication rested with BSRIA.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means electronic or mechanical including photocopying, recording or otherwise without prior written permission of the publisher.

Introduction

The aim of this document is to provide designers with guidance on the provision of both vertical and horizontal holes through concrete elements, both pre-formed and post-formed. The guidance given represents a sound common-sense approach to the design and detailing of holes and openings and should cover most eventualities.

This guide, the third in a series called Interface Engineering Publications, is designed to appeal to both structural and services design engineers. BSRIA and The Concrete Society have pooled their technical knowledge to provide both professions with consistent, interlocking advice.

This advice is often based on material repackaged from existing BSRIA and Concrete Society guidance. Details of the original publications, relevant European and British Standards and other references for further reading are provided at the end of this publication.

A document such as this cannot cover all services to concrete interfaces that may arise, and it is also dangerous to generalise when so many interfaces are specific to a particular context: the nature of the project, the relationship of the professional parties in the contract, and the client requirements for the building, which may be very particular.

In order to demonstrate how many of the key interfaces should be handled, the authors have used a recent project as a case study: The concrete-framed headquarters for the SAS Institute in Buckinghamshire. This project has been used to illustrate practical aspects of the more generic guidance on the integration of services with structure provided in this publication.

Roderic Bunn, BSRIA

Deryk Simpson, The Concrete Society

May 2004

Contents

Photograph: ©Oak Taylor-Smith/MFlip



CASE STUDY

Introduction	1
Early design issues	4
The structural perspective	4
Project pre-planning	4
Post-cut holes	4
Structural surveys	5
The building services perspective	6
Exposed concrete structures	6
Active thermal storage	6
Fixings and fittings	6
Plantrooms and basements	7
Structural design	8
Structural issues	8
Reinforced and pre-stressed concrete	8
Methods of forming holes	8
Shape of penetrations	8
Hole locations in beams	9
Hole size in beams	9
Holes in pre-cast floor units	9
Holes in beam and block floors	10
Holes in reinforced concrete slabs	10
Holes in steel composite decks	10
Post-tensioned floors: pre-formed holes	10
Post-tensioned floors: post-formed holes	12
Pre-formed vertical holes in beams	12
Pre-formed horizontal holes in beams	12
Post-formed vertical holes in beams	14
Post-formed horizontal holes in beams	14
Installing boxes	14
Embedded pipe services in concrete	15

Photograph: ©Oak Taylor-Smith/MFlip



CASE STUDY

Services detailed design	16
Detailed design issues	16
<i>Services penetrating through concrete</i>	16
Reinforcing large openings	16
<i>Externally-bonded fibre composites</i>	18
<i>Near-surface mounted reinforcement</i>	18
Below ground penetrations	18
Testing pipework systems	
Services fixings to concrete	20
Fixing methods	20
<i>Fixing to floor soffits</i>	20
<i>In-situ flat slabs</i>	20
<i>Voided construction</i>	20
<i>Exposed rib construction</i>	21
Integrated systems	24
Principles of thermal storage	24
<i>Active thermal storage: a case study</i>	25
<i>Design issues</i>	26
<i>Installation issues</i>	26
Refurbishment	
Interaction of services with structure	30
<i>Limited storey height</i>	30
<i>Creating openings in slabs</i>	30
<i>Openings in beams and walls</i>	31
Further reading and standards	32
Glossary	33

How to use this guide

Advice about the services engineering requirements of running mechanical and electrical services through concrete elements will be found in **blue-tinted** boxes.

Advice about the structural engineering requirements of running services through concrete elements will be found in **green-tinted** boxes.

Comments marked by **■** link to structural engineering sections listed under *also see*.

Comments marked by **■** link to mechanical engineering sections listed under *also see*.

Comments marked by **■** denote a link common to both specialisms.

Key services watchpoints

- Essential mechanical engineering messages from the guide

Key structural watchpoints

- Essential structural messages from the guide

Also see

- 1** Links to services sections
- 2** Links to structural sections
- 3** Links to common sections

Standards for structural and services design

Further reading to support this guide

Glossary for terms and definitions

Early design issues

The need to cast or cut holes in a concrete element to allow for the passage of services is a common requirement. For some interfaces the problems are easy to resolve, but others require more design expertise and greater involvement between structural and services engineers. For critical areas, like exposed concrete finishes in occupied areas, engineers need to liaise very closely with the client, architect and installing contractors over the details to ensure a functional and aesthetically acceptable solution.



©The Concrete Society.

Figure 1: Even the simplest concrete-framed building has a wealth of integrated engineering services.

The structural perspective

Services and structural engineers need to work together very closely to ensure that the decisions made by the structural engineer will suit the building's comfort requirements. The reverse is also true, as the technical requirements of a particular services solution may dictate elements of the structural design. It is in the client's interest to foster a close working relationship.

It is a common occurrence for holes to be cast or cut into reinforced concrete elements, usually to allow for the passage of services. Wherever possible, the structure should be designed to include a service zone to minimise the need for holes for service runs. Even though this is a common situation faced by designers, guidance on the design and detailing holes is limited. This guide aims to satisfy that need.

Project pre-planning

Pre-planning is preferable to retrospective provision of any holes or openings. Pre-planned holes or openings are those marked on the layout drawings. They have been designed into the structural configuration so that the resulting stresses are distributed and the structure is not compromised.

Circular holes are preferable as square and rectangular holes can induce stress concentrations around their corners, increasing the risk of cracking. Whether the hole is formed in an element at the precast factory or formed *in-situ* makes no difference.

There are three forms of pre-planned holes:

- 1 Holes that are cast at the point of construction of the element and are left open ready to receive services
- 2 services that are cast into the element and remain in position
- 3 areas within a concrete element that are designated for holes to be cut retrospectively.

Occasionally there may be a need for a large hole in an element where standard guidance will not apply. It is not possible to give definitive guidance for such situations because each case will be different.

When large holes are required, an experienced structural engineer should be used to assess the resulting capacity of the element and to design any additional strengthening.

Post-cut holes

- 4 Refurbishment, change of use or poor planning presents other problems, notably when the need for new or extra services

Services engineering issues

Structural issues

requires additional holes to be cut in an existing structure. Questions that need to be addressed include:

- Why is the hole required?
- will the hole be cut through re-inforcement or prestressing strand?
- 5** does the hole and service interface need to be sealed against water, sound or fire?
- is the concrete element pre-stressed?
- did the original design provide nominated zones, free of reinforcing bars or stressed tendons, for services distribution?
- 6** what additional strengthening is required?
- 4** can the services be fixed directly to the concrete or is a separate fixing needed?

Structural surveys

Before undertaking any work that involves cutting into an existing concrete structure (apart from minor fixings), it is important to understand the form of construction and hence how the operation may affect the safety and performance of the structure.

Reinforcement can be in both the top and bottom part of an element.

The location and orientation of steel reinforcing bars and prestressing strands can be determined using a covermeter. A covermeter is a simple, hand-held electro-magnetic device consisting of a search head and a control box. The head is moved across the surface of the concrete and an audible signal or digital readout is used to locate the position of the reinforcing bar. For more details see Concrete Society Technical Report 54, *Diagnosis of deterioration in concrete structures*.

With composite decks the steel soffit will probably impair the reading of a covermeter. However, as they are generally standard details, the location of reinforcing bar is less of a problem. The location and size of the hole is, however, crucial to maintaining structural integrity.

Key structural watchpoints

- Pre-planning is always preferable to retrospective provision of any holes or openings
- The location and size of a hole is crucial to maintaining structural integrity
- Circular holes are preferable as square and rectangular holes can induce stress concentrations around their corners, increasing the risk of cracking
- When large holes are required, structural engineers should assess the resulting capacity of the element and design any additional strengthening
- Structural engineers should determine whether holes need to be sealed against water, sound or fire penetration, and whether additional strengthening of the structure is required

Also see

- 1** Holes in precast floor units, page 9
- 2** Structural design, page 12
- 3** Table 1, page 17
- 4** Services fixings to concrete, page 20
- 5** Figures 14 and 15, page 19
- 6** Figure 13, page 18

Standards on page 32

Further reading on page 32

Glossary on page 33